## **Technical Data Sheet**



# Phenyl Functional Organosilane LS-M11

### **Description:**

Chemical Name: Phenyltrimethoxysilane Synonyms: Trimethoxysilylbenzene Equivalents: Dynasylan 9165; ShinEtsu KBM-103; Momentive Silquest A-153; Dowsil Z-6124 Molecular Structure:

#### **Special Features:**

Molecular Formula:  $C_6H_5Si(OCH_3)_3$ Molecular Weight: 198.29 CAS NO.: 2996-92-1 EINECS NO.: 221-066-9

Phenyl silane used as crosslinking agent for silicone resin and to produce polymer organic silicon compound.

#### **Typical Technical Properties:**

Appearance: Colorless transparent liquid Purity (by GC, %): 98.0 min Refractive Index (20°C): 1.473~1.475 Boiling Point: 211°C Flash Point: 86°C Density: 1.062

#### **Applications:**

1. Mainly used as a crosslinking agent in silicone resins.

2. Used as a raw material for high-molecular organic compounds, especially suitable for the preparation of phenyl silicone oil and silicone rubber.

3. Used as a hydrophobic agent on the surface of inorganic materials, such as wollastonite and aluminum trihydroxide.

4. Used as a dispersant and surface modifier for inorganic materials and can improve thermal stability of other silanes.

5. Suitable as a hydrophobic additive for other silane coupling agents, such as for the production of silane crosslinking adhesives and sealants.

6. Used as an electron donor in the process of polypropylene polymerization.

#### Package & Storage:

In 20kg pail, 190kg drum and 900kg IBC.

Keep in cool, well-ventilated place, and avoid exposure to humidity. Keep away from sunlight and fire sources. Keep in unopened containers, shelf life is 24 months from the date of production. It is shipped as non-hazardous substance.

Storage beyond the shelf life does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Nanjing Silfluo New Material Co., Ltd.

Web: www.silfluosilicone.com Email: inquiry@silfluo.com

The offered information of this docs is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are fully satisfactory for end use. Suggestions of use shall not be taken as inducements to infringe any patent. Please confirm with us prior to any problems.